



# Taśma GERLED® Professional IP20 SMD 2835 12V

GERLED® Professional LED strip  
IP20 SMD 2835 12V

GERLED® Professional striscia LED  
IP20 SMD 2835 12V

GERLED® Professional LED-Streifen  
IP20 SMD 2835 12V



Podwójna warstwa PCB

Double PCB laminate  
PCB a doppio laminate  
Doppelte PCB-Schicht



Stopień ochrony IP20

Protection class  
Grado di protezione (IP)  
IP-Klasse



3 lata

3 lata gwarancji

3 years warranty  
3 anni di garanzia  
3 Jahre Garantie




CRI >85

Współczynnik oddawania barw  
Color rendering index  
Indice di resa cromatica (Ra)  
Farbwiedergabeindex



Zgodność z CE


CE Compliance  
Conformità CE  
CE-Zertifikat



min.  
50 000 h

Żywotność

Life span  
Vitalità  
Lebensdauer



180°

Kąt świecenia

Viewing angle  
Angolo luminoso  
Beleuchtungswinkel



-25°C÷+60°C

Temperatura pracy

Operational temperature  
Temperatura d'esercizio  
Arbeitstemperatur



-40°C÷+80°C

Temperatura magazynowania

Storage temperature  
Temperatura di stoccaggio  
Lagertemperatur



Zgodność z RoHS

RoHS Compliance  
Conformità RoHS  
RoHS-Zertifikat

KOD PRODUKTU PRODUCT CODE CODICE PRODOTTO PRODUKTCODE	BARWA LIGHT COLOR COLORE FARBE	TEMPERATURA BARWOWA COLOR TEMPERATURE TEMPERATURA DI COLORE FARBTEMPERATUR	ILOŚĆ DIOD LED QUANTITY NUMERO DIODI ANZAHL DER LEDS	POBÓR MOCY POWER CONSUMPTION POTENZA NENNLEISTUNG	STRUMIEŃ ŚWIETLNY LUMINOUS FLUX FASCIO LUMINOSO LICHSTROM
05TS12GW03028BC008	BIAŁY CIEPLY WARM WHITE BIANCO CALDO WARMWEISS	2900K-3100K	60 LED/m	4,8 W/m	468 lm/m
05TS12GW06028BC008			120 LED/m	9,6 W/m	905 lm/m
05TS12GW03028BN008	BIAŁY NEUTRALNY NEUTRAL WHITE BIANCO NATURALE NEUTRALWEISS	3900K-4300K	60 LED/m	4,8 W/m	475 lm/m
05TS12GW06028BN008			120 LED/m	9,6 W/m	930 lm/m
05TS12GW03028BZ008	BIAŁY ZIMNY COOL WHITE BIANCO FREDDO KALTWEISS	6000K-6500K	60 LED/m	4,8 W/m	450 lm/m
05TS12GW06028BZ008			120 LED/m	9,6 W/m	900 lm/m
05TS12GW0302812K08	BIAŁY ZIMNY COOL WHITE BIANCO FREDDO KALTWEISS	10000K-13000K	60 LED/m	4,8 W/m	453 lm/m
05TS12GW0602812K08			120 LED/m	9,6 W/m	906 lm/m

## 60 LED/m



sekcja cięcia co 50 mm (3 diody)  
cut section every 50 mm (3 diodes)  
sezione di taglio ogni 50 mm (3 diodi)  
Schnittabschnitt alle 50 mm (3 LEDs)

2 mm  
wysokość  
height  
altezza  
Höhe



8 mm  
szerokość / width / larghezza / Breite

## 120 LED/m



sekcja cięcia co 25 mm (3 diody)  
cut section every 25 mm (3 diodes)  
sezione di taglio ogni 25 mm (3 diodi)  
Schnittabschnitt alle 25 mm (3 LEDs)

2 mm  
wysokość  
height  
altezza  
Höhe



8 mm  
szerokość / width / larghezza / Breite