



Taśma GERLED® Professional IP65 SMD 2835 12V

GERLED® Professional LED strip
IP65 SMD 2835 12V

GERLED® Professional striscia LED
IP65 SMD 2835 12V

GERLED® Professional LED-Streifen
IP65 SMD 2835 12V



Podwójna warstwa PCB

Double PCB laminate
PCB a doppio laminate
Doppelte PCB-Schicht



Stopień ochrony IP65

Protection class
Grado di protezione (IP)
IP-Klassee



3 lata gwarancji

3 years warranty
3 anni di garanzia
3 Jahre Garantie



Współczynnik oddawania barw

Color rendering index
Indice di resa cromatica (Ra)
Farbwiedergabeindex




Zgodność z CE

CE Compliance
Conformità CE
CE-Zertifikat



Zywność

Life span
Vitalità
Lebensdauer



Kąt świecenia

Viewing angle
Anglo luminoso
Beleuchtungswinkel



Temperatura pracy

Operational temperature
Temperatura d'esercizio
Arbeitstemperatur



Temperatura magazynowania

Storage temperature
Temperatura di stoccaggio
Lagertemperatur



Zgodność z RoHS

RoHS Compliance
Conformità RoHS
RoHS-Zertifikat

KOD PRODUKTU PRODUCT CODE CODICE PRODOTTO PRODUKTCODE	BARWA LIGHT COLOR COLORE FARBE	TEMPERATURA BARWOWA COLOR TEMPERATURE TEMPERATURA DI COLORE FARBTEMPERATUR	ILOŚĆ DIOD LED QUANTITY NUMERO DIODI ANZAHL DER LEDS	POBÓR MOCY POWER CONSUMPTION POTENZA NENNLEISTUNG	STRUMIEŃ ŚWIETLNY LUMINOUS FLUX FASCIO LUMINOSO LICHSTROM
05TS12GZ03028BC008	BIAŁY CIEPLY WARM WHITE BIANCO CALDO WARMWEISS	2800K-3200K	60 LED/m	4,8 W/m	370 lm/m
05TS12GZ06028BC008			120 LED/m	9,6 W/m	578 lm/m
05TS12GZ03028BN008	BIAŁY NUETRALNY NEUTRAL WHITE BIANCO NATURALE NEUTRALWEISS	3900K-4300K	60 LED/m	4,8 W/m	397 lm/m
05TS12GZ06028BN008			120 LED/m	9,6 W/m	692 lm/m
05TS12GZ03028BZ008	BIAŁY ZIMNY COOL WHITE BIANCO FREDDO KALTWEISS	6000K-6500K	60 LED/m	4,8 W/m	337 lm/m
05TS12GZ06028BZ008			120 LED/m	9,6 W/m	674 lm/m

60 LED/m



sekcja cięcia co 50 mm (3 diody)
cut section every 50 mm (3 diodes)
sezione di taglio ogni 50 mm (3 diodi)
Schnittabschnitt alle 50 mm (3 LEDs)



120 LED/m



sekcja cięcia co 25 mm (3 diody)
cut section every 25 mm (3 diodes)
sezione di taglio ogni 25 mm (3 diodi)
Schnittabschnitt alle 25 mm (3 LEDs)

