



Standard: IEC60169  
 Impedance: 50 Ω  
 Frequency range: 0 ~ 6GHz  
 Insulation Resistance: ≥ 5000M Ω  
 Medium pressure resistance: 1000V (AC 有效值)  
 Internal conductor separation force: ≥ 0.28 N  
 Axial holding force: ≥ 22 N  
 Endurance distance of connecting mechanism: ≥ 1.7 N · m  
 Mechanical life: ≥ 500 次  
 Temperature range: -55℃ ~ 165℃  
 Contact resistance: Between outer conductors: < 2m Ω,  
 Between inner conductors: < 3m Ω

5	ST8.034.1342	外壳	HPb59-1	金	1	
4	ST8.034.006E	外壳	HPb59-1	金	1	
3	ST7.890.107	绝缘体	PTFE		1	
2	ST7.890.012	绝缘体	PTFE		1	
1	ST7.744.246	插孔	HPb59-1	金	1	
序	图号/编	零件名	材质	涂	覆	备注

版次	V1.0	比例	编号	ST3.660.190
投影			规格	SMA-KWE
1. X.X±0.2		4.去除锐边最大0.1		
2.X.XX?.1		5.表面粗糙度Ra3.2		
3.角度?°		6.倒角C0.15MAX		
* 为重点			单	mm