

NIEPALNE DRUTOWE REZYSTORY MOCY

NON FLAMMABLE WIRE WOUND POWER RESISTORS

moc znamionowa power rating	wymiary dimensions (mm)											zakres rezystancji resistance range
	A±1	B±2	C±2	D±0.1	E±0.2	F±1	G±2	H±2	I±2	J±2	K±0.1	
10W	12.5	45	35	2.1	4	10	55	56	57	30	4	1Ω...10kΩ
20W	16.5	60	45	3.0	5	12	70	84	100	37	4	1Ω...20kΩ
30W	16.5	80	65	3.0	5	12	90	104	120	37	4	1Ω...30kΩ
40W	16.5	110	95	3.0	5	12	120	134	150	37	4	1Ω...40kΩ
50W	25	110	92	5.2	8	19	120	142	164	58	6	0.1Ω...50kΩ
60W	28	90	72	5.2	8	17	101	123	145	60	6	0.1Ω...60kΩ
80W	28	110	92	5.2	8	17	121	143	165	60	6	0.1Ω...80kΩ
100W	28	140	122	5.2	8	17	151	173	195	60	6	0.1Ω...100kΩ
120W	28	160	142	5.2	8	17	171	193	215	60	6	0.1Ω...120kΩ
150W	28	195	177	5.2	8	17	206	229	250	60	6	0.1Ω...150kΩ
160W	35	185	167	5.2	8	17	197	217	245	75	8	0.1Ω...160kΩ
200W	35	210	192	5.2	8	17	222	242	270	75	8	0.1Ω...200kΩ
250W	40	210	188	5.2	10	18	222	242	270	77	8	0.5Ω...250kΩ
300W	40	260	238	5.2	10	18	272	292	320	77	8	0.5Ω...300kΩ
400W	40	330	308	5.2	10	18	342	380	390	77	8	0.5Ω...400kΩ
500W	50	330	304	6.2	12	28	346	367	399	105	9	0.5Ω...500kΩ

