

Part Number	Primary Voltage (V)	Secondary Voltage (V)	Secondary Current (mA)	No-load Voltage (V)	Ambient Temperature (°C)	Rated Power (VA)	Dimension H Max. (mm)	Weight Approx. (g)	Agency Approval
TR Z00.35/06b II	230	6	58	9	T 70/B	0.35	16	25	VDE CE
TR Z00.35/09b II	230	9	39	13.5	T 70/B	0.35	16	25	
TR Z00.35/12b II	230	12	29	17.9	T 70/B	0.35	16	25	
TR Z00.35/15b II	230	15	23	22.4	T 70/B	0.35	16	25	
TR Z00.35/18b II	230	18	19	26.8	T 70/B	0.35	16	25	
TR Z00.35/24b II	230	24	15	35.8	T 70/B	0.35	16	25	
TR Z00.35/2x06b II	230	2×6	2×29	2×9	T 70/B	0.35	16	25	
TR Z00.35/2x09b II	230	2×9	2×19	2×13.5	T 70/B	0.35	16	25	
TR Z00.35/2x12b II	230	2×12	2×14	2×17.9	T 70/B	0.35	16	25	
TR Z00.35/2x15b II	230	2×15	2×12	2×22.4	T 70/B	0.35	16	25	
TR Z00.35/2x18b II	230	2×18	2×9	2×26.8	T 70/B	0.35	16	25	
TR Z00.35/2x24b II	230	2×24	2×7	2×35.8	T 70/B	0.35	16	25	