



### Technical Data

**Material:**

Body: PA66 UL94 V-0.

Conductor: Copper, Tin Plated.

Spring: SUS 301.

**Electrical:**

Current rating: 41A.

Contact resistance: 20 mΩ Max.

**Mechanical:**

Connection Capacity: 24-10AWG.

Stripping Length: 14mm.

Operating temperature: -45° C to +105° C.

REV.	EQD.NO.	REVISE NO.	REVISED	APPD.
R1	版次	版本号	修改者	核准
	DRAWING			



**ZHEJIANG UTILITY ELECTRICAL CO., LTD**  
**浙江尤提乐电气有限公司**

<b>&gt;120</b>	<b>±0.50</b>	<b>TYPE NO.</b>	<b>名称:</b>	<b>TITLE:</b>
<b>&gt;30~120</b>	<b>±0.30</b>	JUT14-6PE	型号:	Customer Drawing
<b>&gt;6~30</b>	<b>±0.20</b>		核准:	
<b>0~6</b>	<b>±0.10</b>		审核:	
<b>ANGLE</b>	<b>±1°</b>	<b>CHKD.</b>	设计:	<b>DWG. NO.:</b>
<b>MATL</b>		DR.	Jammy.ling	C-DW2118-0
材质:				<b>SCALE:</b> FULL
				比例: 1/1
				<b>PAGE:</b> 1/1
				页码: R1
				<b>REV.:</b> R1
				版次: