



TYPE	ZUG-G2,5	ZUG-G4	ZUG-G10	ZUG-G16
Catalogue number	11-007	11-010	11-020	11-037
Colour	<ul style="list-style-type: none"> yellow-1 ● white-2 ○ black-3 ● green-5 ● blue-6 ● red-7 ● grey-8 ● 	<ul style="list-style-type: none"> yellow-1 ● white-2 ○ black-3 ● green-5 ● blue-6 ● red-7 ● grey-8 ● 	<ul style="list-style-type: none"> yellow-1 ● white-2 ○ black-3 ● green-5 ● blue-6 ● red-7 ● grey-8 ● 	<ul style="list-style-type: none"> yellow-1 ● white-2 ○ black-3 ● green-5 ● blue-6 ● red-7 ● grey-8 ●
Standard	IEC 60947-7-1	IEC 60947-7-1	IEC 60947-7-1	IEC 60947-7-1
Nominal cross-section	2,5mm ²	4mm ²	10mm ²	16mm ²
Nominal connectivity: wire/cord	0,5...2,5mm ²	0,5...4mm ²	0,5...10 / 0,5...6mm ²	1,5...16 / 1,5...10mm ²
Nominal voltage of insulation	690V	690V	690V	690V
Nominal impulse withstand voltage	6kV	6kV	6kV	6kV
Nominal continuous current	24A	32A	57A	76A
Terminal torque	0,4Nm	0,5Nm	1,2Nm	2,0Nm
Stripping length	8mm	8mm	10mm	12mm
Width	5,2mm	6,4mm	8mm	12mm
Insulating material	polyamide	polyamide	polyamide	polyamide
Ambient temperature	-25...+100°C	-25...+100°C	-25...+100°C	-25...+100°C
Weight	6g	7g	13g	24g
Package	60pcs.	50pcs.	50pcs.	30pcs.

Equipment and accessories

EQUIPMENT	PAGE	ZUG-G2,5	ZUG-G4	ZUG-G10	ZUG-G16
Mounting rails	200	TS32/AL, TS35	TS15/AL, TS32/AL, TS35	TS15/AL, TS32/AL, TS35	TS32/AL, TS35
HOLDERS	49	KU-1/35, KU-2/35	KU-15, KU-1/35	KU-15, KU-1/35	KU-1/35, KU-2/35, KU-3/35
End section	50	PSU-4	PSU-4	PSU-10	PSU-16
Short-circuiting connectors	53	ZKU-2,5/...	ZKU-4/...	ZKU-10/...	ZKU-16/...
Separators	50	PSU-10	PSU-10	PSU-16	—
Markers	48	DK/Z-5	DK/Z-5, DK/Z-6	DK/Z-5, DK/Z-6	DK/Z-5, DK/Z-6
Protection covers	50	—	OZZ-3	—	—