


# RING TERMINALS

- Material
- Insulation: Vinyl
- Terminal Body: Copper
- Plating: Tin



ITEM NO.	STUD SIZE		DIMENSIONS								COLOR	EXPLANATION
	Metric	American	d2	W	F	L	H	d1	D	T		
RV1.25-3.2	3	#4	3.2	5.7	4.95	17.8	10	1.7	4.2	0.8	RED	PVC 75°C Wire range : 0.5-1.5mm <sup>2</sup> A.W.G.:(22-16) Max.current=19A
RV1.25-3.7S	3.5	#6	3.7									
RV1.25-3.7M	3.5	#6	3.7	6.6	6.3	19.6						
RV1.25-3.7L	3.5	#6	3.7	8.0	7.0	21.0						
RV1.25-4S	4	#8	4.3	6.6	6.3	19.6						
RV1.25-4L	4	#8	4.3	8.0	7.0	21.0						
RV1.25-5	5	#10	5.3									
RV1.25-5L	5	#10	5.3	9.5	7.5	22.3						
RV1.25-6	6	1/4"	6.5	11.6	11.2	27.0						
RV1.25-8	8	5/16"	8.5	13.6	13.9	30.7						
RV1.25-8L	8	5/16"	8.5									
RV1.25-10	10	3/8"	10.5	19.2	16.0	35.6						
RV1.25-12	12	1/2"	13.0	27.0	21.0	44.5						
RV1.25-14	14	9/16"	15.0									
RV1.25-16	16	5/8"	17.0	27.0	21.0	44.5						
RV1.25-20	20	3/4"	21.0									
RV2-3.2S	3	#4	3.2	5.5	4.8	17.6	10	2.3	4.7	0.8	BLUE	PVC 75°C Wire range : 1.5-2.5mm <sup>2</sup> A.W.G.:(16-14) Max.current=27A
RV2-3.2	3	#4	3.2	6.6	6.4	19.7						
RV2-3.5	3.5	#6	3.7									
RV2-3.7M	3.5	#6	3.7	6.6	7.9	21.2						
RV2-3.7L	3.5	#6	3.7	8.5	7.75	22.0						
RV2-4S	4	#8	4.3	6.6	7.9	21.2						
RV2-4L	4	#8	4.3	8.5	7.75	22.0						
RV2-5S	5	#10	5.3									
RV2-5L	5	#10	5.3	9.5	7.5	22.3						
RV2-6	6	1/4"	6.5	12.0	11.0	27.0						
RV2-8	8	5/16"	8.5	12.0	11.0	27.0						
RV2-8L	8	5/16"	8.5	13.6	13.9	30.7						
RV2-10	10	3/8"	10.5									
RV2-12	12	1/2"	13.0	19.2	16.0	35.6						
RV2-14	14	9/16"	15.0	27.0	21.0	44.5						
RV2-16	16	5/8"	17.0									
RV2-20	20	3/4"	21.0									
RV3.5-4	4	#8	4.3	8.0	7.7	24.7	13	2.9	6.2	1.0	BLACK	PVC 75°C Wire range : 2.5-4mm <sup>2</sup> A.W.G.:(14-12) Max.current=37A
RV3.5-5.5S	5	#10	5.3									
RV3.5-5.5	5	#10	5.3	12.0	9.4	28.4						
RV3.5-6	6	1/4"	6.5	15.0	13.5	34.0						
RV3.5-8	8	5/16"	8.5									
RV3.5-10	10	3/8"	10.5	19.2	16.0	38.6						
RV5.5-3.2	3	#4	3.2	13	3.4	6.5	1.0	YELLOW	PVC 75°C Wire range : 4-6mm <sup>2</sup> A.W.G.:(12-10) Max.current=48A			
RV5.5-3.5	3.5	#6	3.7							7.2	5.9	22.5
RV5.5-4S	4	#8	4.3							9.5	8.85	26.6
RV5.5-4L	4	#8	4.3									
RV5.5-5	5	#10	5.3							12.0	10.5	29.5
RV5.5-6	6	1/4"	6.5							15.0	13.5	34.0
RV5.5-8	8	5/16"	8.5									
RV5.5-10	10	3/8"	10.5							19.2	16.0	38.6
RV5.5-12	12	1/2"	13.0							32.0	25.2	54.2
RV5.5-14	14	9/16"	15.0									
RV5.5-16	16	5/8"	17.0	32.0	25.2	54.2						
RV5.5-20	20	3/4"	21.0									

