

Specification Sheet

Terminal Pad Solderability:
Meets EIA Specification RS186-9E
And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:
Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:

Part Identification

V= 005




TABLE I. DIMENSIONS:

Model	Marking	A		B		C		D	E
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Min.
BpS03-050-15	V	1.45	1.85	0.65	1.05	0.40	1.00	0.15	0.10

Unit:mm

TABLE II. PERFORMANCE RATINGS:

Model	Marking	V_{max} (Vdc)	I_{max} (A)	I_{hold} @25°C (A)	I_{trip} @25°C (A)	P_d Typ. (W)	Maximum Time To Trip		Resistance	
							Current (A)	Time (Sec)	$R_{i_{min}}$ (Ω)	$R_{1_{max}}$ (Ω)
							BpS03-050-15	V	15.0	40

Order Information

Packaging

SMD0603	005	Tape & Reel Quantity	
Product name	Hold	Max	5,000 pcs/reel
Size 1508 mm / 0603 mils	Current	voltage	
SMD: surface mount device	0.05A		

Recognition: UL Approved.