

**P/N: WTL9S12577**

**Resistance Welded HC-49/S Low Profile Package**



Customer	WTL
	Approved by: XoXo Lee
	Checked by: Susan He
	Issued by: Sheryl Xia

# SPECIFICATION

**深圳市维拓精电科技有限公司**

**WTL International Limited**

**Tel: 86-755-8267 7582 Fax: 86-755-82677582**

**[www.wtlcrystals.com](http://www.wtlcrystals.com) email: [wtl@wtlcrystals.com](mailto:wtl@wtlcrystals.com)**

**FEATURE**

- Standard height 3.5mm, the part is compact at about one-fourth of the HC-49/U package
- A resistance weld completely sealed type
- Good stability and high reliability
- Copes with high density mounting and is the optimum for mass production

**ELECTRICAL SPECIFICATIONS**

Nominal frequency	8.000MHz
Oscillation mode	See below table
Operating temperature range	-20°C--+70°C
Storage temperature range	-40°C--+85°C
Frequency tolerance	±20ppm
Freq. Temp characteristics	±30ppm
Load capacitance	18pF
Equivalent series resistance	See below table
Parallel capacitance(Co)	7PF Max
Drive level	100 μW Typical
Insulation resistance	More than 500MΩ AT DC100V

**EQUIVALENT SERIES RESISTANCE(ESR) AND OSCILLATION MODE**

Frequency Range	E.S.R (Ω)	Mode	Frequency Range	E.S.R (Ω)	Mode
3.000MHz~5.999MHz	150Max	Fundamental/AT	24.000MHz~40.320MHz	30Max	Fundamental/ BT
6.000MHz~7.999MHz	60Max	Fundamental/AT	24.000MHz~29.999MHz	100Max	Third Overtone /AT
8.000MHz~15.999MHz	50Max	Fundamental/AT	30.000MHz~49.999MHz	80Max	Third Overtone /AT
16.000MHz~30.000MHz	30Max	Fundamental/AT	50.000MHz~100.000MHz	60Max	Third Overtone /AT

**P/N: WTL9S12577**

**Resistance Welded HC-49/S Low Profile Package**



**Dimension**

# HC-49S

