

Product Number: AN155
Product Name: Antenna

Specification For Approval

Date: 2019-09-19

File No.: 190919001

Version: 1.0

Customer : _____

Customer P/N : ST-ANGSM-3RSR

P/N : AN155

Description : Ant GSM 3dBi RP-SMA Male Rotat 155x13mm

Checked By:

Customer Approved By:

Product Number: AN155
Product Name: Antenna

Index:

- 1. Revision History / Page 3**
- 2. Specification / Page 4**
- 3. Characteristics and Reliability Test / Page 5**
- 4. Antenna - S Parameter Test Data / Page 6**
- 5. Antenna - Radiation Pattern Test Data / Page 7 ~ 8**
- 6. Mechanical and Packing Drawing / Page 9 ~ 10**

Product Number: AN155

Product Name: Antenna


1. Revision History

Revision	Date	Notification	Description
1.0	2019-09-19	初版	

Product Number: AN155

Product Name: Antenna

2. Specification

Sample Photo	
	
A. Electrical Characteristics	
Frequency	824 ~ 960 MHz 1710 ~ 2170 MHz
S.W.R.	≤ 6.0 @ 824 ~ 960 MHz \leq 4.0 @ 1710 ~ 2170 MHz Tested at 290mm Square Ground Plane
Antenna Average Gain	- 12 ~ - 9 dBi @ 824 ~ 960 MHz - 7 ~ -5 dBi @ 1710 ~ 2170 MHz Tested at 290mm Square Ground Plane
Polarization	Linear
Impedance	50 Ohm
B. Material & Mechanical Characteristics	
Material of Radiator	Cu Material of
Plastic	Body: TPEE Hinge: ABS Holder: POM
Cable Type	RG-178
Connector Type	RP-SMA Male
C. Environmental	
Operation Temperature	- 40 °C ~ + 65 °C
Storage Temperature	- 40 °C ~ + 80 °C
Antenna Color Storage life	< 2 year

Product Number: AN155

Product Name: Antenna

3. Characteristics and Reliability Test

Test Items 測試項目		Test Condition and Procedure 測試方法	Requirements 要求	Result 結果
C1	V.S.W.R. 電壓駐波比	Set DUT on Network Analyzer; make individual calibration to test 設置網路分析儀參數進行測試	Directive DUT specification 符合待測物規範	PASS
C2	Insertion Loss 插入損失	Set DUT on Network Analyzer; make individual calibration to test 設置網路分析儀參數進行測試	Directive DUT specification 符合待測物規範	N/A
C3	Antenna Gain 天線增益	Set DUT on Antenna Chamber; make individual calibration to test 設置天線暗室參數進行測試	Directive DUT specification 符合待測物規範	PASS
C4	Voltage Breakdown 耐電壓	Test voltage should be applied between insulated portions, or between ground as specified. 在絕緣部分測試電壓,或指定接地面之間	Max Voltage \geq 500 V or directive material specification 最大電壓 \geq 500V 或符合材料規範	N/A
C5	Insulation Resistance 絕緣阻抗	Set Voltage: 500 \pm 50V; between the insulated portions, or between ground as specified. 設置電壓 500 \pm 50V,在絕緣部份測試或指定接地面之間	Resistance \geq 500 M ohm or directive material specification 阻抗 \geq 500M ohm 或符合材料規範	N/A
C6	Contact Resistance 接觸阻抗	Air Temp: 26°C; measured with test equipment 室溫 26°C, 指定量測設備	Directive material specification 符合材料規範	N/A
M1	Vibration 震動	GB / T2423.48-2008 Amplitude: 0.03 inch (1.5mm); Freq: 20 to 80 to 20 Hz 3 directions; 2 hours for each direction 振幅 1.5mm; 頻率 20~80~20Hz; 3 個方向各 2H	1. No Visual Damage 2. Frequency Tol. \leq 5% 無明顯外觀不良; 頻率偏移 \leq 5%	PASS
M2	Random Drop 跌落	GB / T2423.8-1995 Single : Height: 1.0 Meter; 3 directions; 1 time for each direction 單支天線, 高 1m; 3 個方向各 1 次	1. No parts separated、fracture 2. Frequency Tol. \leq 5% 產品無脫落、斷裂; 頻率偏移 \leq 5%	PASS
		Packing : Height: 0.76 Meter; 1 corner, 3 edges, 6 surface 包裝: 高 0.76m, 一角、三棱、六面各一次		PASS
		Antenna+Machine: Height: 0.76 Meter; 1 corner, 3 edges, 6 surface. 整機: 高 0.76m, 一角、三棱、六面各一次	N/A	
M3	Solderability	GB / T2423.28-2005	Tin evenly on full	N/A

Product Number: AN155


Product Name: Antenna

	可焊性	Temp: 260±5° C;Duration: 5 seconds 溫度 260±5° C;持續 5 秒	上錫均勻飽滿	
M4	Pull test T 拉力	Holding with individual specification; force applied to axis of terminal .單獨定義產品端子拉力	1. Directive DUT specification 2. Frequency Tol.≤5% 符合待測物規範;頻率偏移≤5%	PASS
M5	Torque Test 扭力	Holding with individual specification; applied clockwise and counterclockwise to the axis of terminal 單獨定義產品端子之順時針及逆時針扭力	1. Directive DUT specification 2. Frequency Tol.≤ 5% 符合待測物規範;頻率偏移≤5%	PASS
M6	Dimension 尺寸	Inspection of dimension, color, material, package, surface process.检查尺寸,颜色,材料,包装,表面處理	Directive DUT specification 符合待測物規範	PASS
E1	Waterproof 防水	With Reference to IEC 60529 // IP Code Definition 參考 IEC60529 IP 定義	Directive DUT specification 符合待測物規範	N/A
E2	Salt Spray 鹽霧	GB / T 2423.17-2008 Temp: 35°C; RH: ≥ 95%; NaCl solution: ≥ 5%;Time: 24H 溫度 35°C ; 濕度≥95%;鹽水濃度≥5% ; 測試 24H	1. No Visual Damage 2. Frequency Tol.≤5% 無明顯外觀不良;頻率偏移≤5%	PASS
E3	Temperature and Humidity Chamber 恒溫恒濕	GB / T 2423.3-2006 Temp: 80°C / 12 H; -40°C / 12H RH: ≥ 90 %; Time: 24H 溫度 80°C 測試 12H 轉-40°C 測試 12H; 濕度≥ 90 %; 時間 24H	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.≤5% 恢復 2H 后, 無明顯外觀不良;頻率偏移≤5%	PASS
E4	Thermal Shock 冷熱衝擊	GB / T 2423.22 - 2008 - 40°C (30 minutes) to + 80°C (30 minutes) ; Cycles: 24 - 40°C 測試 30 分轉 80°C 測試 30 分為一個週期; 共 24 週期	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.≤5% 恢復 2H 后, 無明顯外觀不良;頻率偏移≤5%	PASS
E5	Aging test 老化	GB / T 2423.2 - 2008 Temp: 80°C; Time: 24 hours 溫度 80°C , 測試 24H	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.≤5% 無明顯外觀不良;頻率偏移≤5%	PASS
E6	High Temp 高溫	Temp. 270±10°C ; Times : 120 seconds 溫度 270±10°C , 測試時間 120 秒	No Visual Damage 無明顯外觀不良	N/A
R1	RoHS	With Reference to IEC 62321:2008 with flow chart 參考 IEC 62321 測試流程	Directive RoHS 2011/65/EU 符合 RoHS 2011/65/EU 標準	PASS
R2	PFOS	With Reference to USA EPA 3550C:1996 by LC/MS 參考 USA EPA 3550C 測試流程	Directive RoHS 2006/122/EC 符合 RoHS 2011/65/EU 標準	PASS

Product Number: AN155

Product Name: Antenna


4. Antenna - S Parameter Test Data



Product Number: AN155


Product Name: Antenna

5. Antenna - Radiation Pattern Test Data



Frequency	824	839	854	869	884	899	914	929	944	959	960
TRP (dBm)	-14.84	-14.67	-14.38	-13.69	-13.5	-13.57	-13.63	-13.46	-13.5	-12.92	-12.88
Peak EIRP (dBm)	-11.93	-12.05	-11.77	-10.86	-10.6	-10.81	-10.72	-10.51	-10.42	-9.62	-9.57
NHPRP +/- 45 (degree)	-14.9	-14.72	-14.42	-13.73	-13.52	-13.58	-13.63	-13.44	-13.45	-12.82	-12.78
NHPRP +/- 30 (degree)	-15.6	-15.45	-15.19	-14.52	-14.33	-14.4	-14.44	-14.27	-14.33	-13.75	-13.71
E-Theta Peak Gain (dBi)	-17.35	-17.01	-16.55	-16.35	-16.35	-16.53	-16.01	-15.34	-15.35	-14.65	-14.6
E-Phi Peak Gain (dBi)	-12.55	-12.23	-11.9	-11.05	-10.79	-10.99	-11.25	-10.91	-10.68	-9.88	-9.83
E-Total Peak Gain (dBi)	-11.93	-12.05	-11.77	-10.86	-10.6	-10.81	-10.72	-10.51	-10.42	-9.62	-9.57
Directivity (dBi)	2.91	2.62	2.61	2.83	2.9	2.76	2.92	2.95	3.08	3.29	3.3
Efficiency (%)	3.28	3.41	3.65	4.28	4.47	4.4	4.33	4.5	4.47	5.11	5.16

Product Number: AN155
Product Name: Antenna




Frequency	1710	1760	1800	1850	1880
TRP (dBm)	-12.14	-11.51	-11.56	-11.52	-10.59
Peak EIRP (dBm)	-6.18	-6.15	-5.81	-6.32	-5.27
NHPRP +/- 45 (degree)	-11.89	-11.25	-11.38	-11.49	-10.69
NHPRP +/- 30 (degree)	-14.46	-13.79	-13.88	-13.76	-12.96
E-Theta Peak Gain (dBi)	-13.8	-13.49	-13.7	-14.31	-14.32
E-Phi Peak Gain (dBi)	-6.6	-6.31	-5.83	-6.45	-5.36
E-Total Peak Gain (dBi)	-6.18	-6.15	-5.81	-6.32	-5.27
Directivity (dBi)	5.96	5.36	5.75	5.2	5.32
Efficiency (%)	6.1	7.06	6.98	7.04	8.73

RoHS

Compatible



SIGN	DATE	DESCRIPTION	APPROVER
△			
△			
△			



Note:
 1.Take " * "is the important dimension.
 2.Tolerance:Unmarked tolerance refer to the standard tolerance please.

4	SMA-MC-920C-A	RP-SMA Male	CU	Black	1
3	AN0304-T07B	Body3	ABS	Black	1
2	AN9201-06B	Body2	ABS	Black	1
1	AN1701-01B	Body1	TPEE	Black	1
No.	Part Number	Description	Material	Finished	Q'ty

TITLE: GSM Antenna RP-SMA Male					
PART NO.: AN155			CUSTOMER P/N: /		
APP BY	CHK BY	RF BY	DES BY		Tolerance
LQ			DJC	UNITS: mm SCALE: 1/1 REVISION: A	X.X ±0.5
2019-09-19			2019-09-19		X.XX ±0.2
					X° ±1

產品包裝規範

PACKING CRITERION






Date: 2019-09-19

Page: 1 of 1


Part Number : AN155	Revision : A
Name: Antenna	Customer : ALL

1.





R-PE-BAG-300245006 50PCS/BAG

2.



SIZE: 29*23*32.5CM
600 PCS/BOX

3.



APPROVED BY : LQ

CHECKED BY : DJC

DESIGNED BY : _____