


3-Terminal 1.5A Positive Voltage Regulator

Description


The 78XX series of three-terminal positive regulators are available in the TO-220AB /TO-252 package with several fixed output voltages making it useful in a wide range of applications.

Features

- ◆ Output Current up to 1.5A
- ◆ Output Voltages of 5,6,8,9,10,12,15V
- ◆ Thermal Overload Protection
- ◆ Short Circuit Protection
- ◆ Output Transistor Safe Operating area (SOA)Protection



Internal Block Diagram



Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Input Voltage	V_{IN}	35	V
Thermal Resistance Junction-Cases (TO-220AB)	$R_{\theta JC}$	5	°C/W
Thermal Resistance Junction-Air	TO-220AB	65	°C/W
	TO-252	92	
Operating Temperature Range	T_{OPR}	0 ~ +125	°C
Storage Temperature Range	T_{STG}	-55 ~ +150	°C

Note 1 Absolute maximum ratings are those values beyond which damage to the device may occur. The datasheet specifications should be met, without exception, to ensure that the system design is reliable over its power supply, temperature, and output/input loading variables. Fairchild does not recommend operation outside datasheet specifications.

Electrical Characteristics (7805AD/AT)

($V_I = 10V$, $I_O = 0.5A$, $C_I = 0.33\mu F$, $C_O = 0.1\mu F$, $T_J = -40^\circ C$ to $125^\circ C$, unless otherwise specified)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Output Voltage	V_O	$T_J = 25^\circ C$, $I_O = 5mA \sim 1A$	4.80	5.0	5.20	V
		$V_I = 7V \sim 20V$, $I_O = 5mA \sim 1A$	4.75	5.0	5.25	V
Line Regulation ②	ΔV_O	$T_J = 25^\circ C$	$V_I = 7V \sim 25V$		100	mV
			$V_I = 8V \sim 12V$		50	
Load Regulation ②	ΔV_O	$T_J = 25^\circ C$	$I_O = 5mA \sim 1A$		100	mV
			$I_O = 0.25A \sim 0.75A$		50	
Quiescent Current	I_Q	$T_J = 25^\circ C$			8.0	mA
Quiescent Current Change	ΔI_Q	$I_O = 5mA \sim 1A$			0.5	mA
		$V_I = 7V \sim 25V$			1.3	
Output Voltage Drift ③	$\Delta V / \Delta T$	$I_O = 5mA$		-0.8		mV/ $^\circ C$
Output Noise Voltage	V_N	$10Hz \leq f \leq 100KHz$		42		$\mu V/V_O$
Ripple Rejection ③	RR	$f = 120Hz$, $V_I = 8V \sim 18V$	62	73		dB
Output Resistance ③	R_O	$f = 1kHz$		15		m Ω
Short Circuit Current	I_{SC}	$T_J = 25^\circ C$, $V_I = 30V$		230		mA
Peak Out Current ③	I_{PK}	$T_J = 25^\circ C$		1.8		A
Dropout Voltage	V_d	$T_J = 25^\circ C$, $I_O = 1A$		2.0		V

Note 2: Load and line regulation are specified at constant junction temperature. Changes in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Note 3: These parameters, although guaranteed, are not 100% tested in production.

Electrical Characteristics (7806AD/AT)

(V_I = 11V, I_o = 0.5A, C_I = 0.33μF, C_O = 0.1μF, T_j = -40 to 125°C, unless otherwise specified)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Output Voltage	V _O	T _j = 25°C, I _o = 5mA ~ 1A	5.76	6.0	6.24	V
		V _I = 8V ~ 12V, I _o = 5mA ~ 1A	5.70	6.0	6.30	V
Line Regulation ④	ΔV _O	T _j = 25°C	V _I = 8V ~ 25V		120	mV
			V _I = 9V ~ 13V		60	
Load Regulation ④	ΔV _O	T _j = 25°C,	I _o = 5mA ~ 1A		120	mV
			I _o = 0.25A ~ 0.75A		60	
Quiescent Current	I _Q	T _j = 25°C			8.0	mA
Quiescent Current Change	ΔI _Q	I _o = 5mA ~ 1A			0.5	mA
		V _I = 8V ~ 25V			1.3	
Output Voltage Drift ⑤	ΔV / ΔT	I _o = 5mA		-0.8		mV/°C
Output Noise Voltage	V _N	10Hz ≤ f ≤ 100KHz		76		μV/V _O
Ripple Rejection ⑤	RR	f = 120Hz, V _I = 8V ~ 18V	55	71		dB
Output Resistance ⑤	R _O	f = 1kHz		19		mΩ
Short Circuit Current	I _{SC}	T _j = 25°C, V _I = 30V		230		mA
Peak Out Current ⑤	I _{PK}	T _j = 25°C		1.8		A
Dropout Voltage	V _d	T _j = 25°C, I _o = 1A		2.0		V

Note 4: Load and line regulation are specified at constant junction temperature. Changes in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Note 5: These parameters, although guaranteed, are not 100% tested in production.

Electrical Characteristics (7808AD/AT)

(V_I = 14V, I_O = 0.5A, C_I = 0.33μF, C_O = 0.1μF, T_J = -40 to 125°C, unless otherwise specified)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Output Voltage	V _O	T _J = 25°C, I _O = 5mA ~ 1A	7.68	8.0	8.32	V
		V _I = 10.5V ~ 23V, I _O = 5mA ~ 1A	7.60	8.0	8.40	V
Line Regulation ⑥	ΔV _O	T _J = 25°C	V _I = 10.5V ~ 25V		160	mV
			V _I = 11.5V ~ 17V		80	
Load Regulation ⑥	ΔV _O	T _J = 25°C,	I _O = 5mA ~ 1A		160	mV
			I _O = 0.25A ~ 0.75A		80	
Quiescent Current	I _Q	T _J = 25°C			8.0	mA
Quiescent Current Change	ΔI _Q	I _O = 5mA ~ 1A			0.5	mA
		V _I = 10.5V ~ 25V			1.0	
Output Voltage Drift ⑦	ΔV / ΔT	I _O = 5mA		-0.8		mV/°C
Output Noise Voltage	V _N	10Hz ≤ f ≤ 100KHz		52		μV/V _O
Ripple Rejection ⑦	RR	f = 120Hz, V _I = 11.5V ~ 21.5V	56	73		dB
Output Resistance ⑦	R _O	f = 1kHz		17		mΩ
Short Circuit Current	I _{SC}	T _J = 25°C, V _I = 30V		230		mA
Peak Out Current ⑦	I _{PK}	T _J = 25°C		1.8		A
Dropout Voltage	V _d	T _J = 25°C, I _O = 1A		2.0		V

Note 6: Load and line regulation are specified at constant junction temperature. Changes in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Note 7: These parameters, although guaranteed, are not 100% tested in production.

Electrical Characteristics (7809AD/AT)

(V_I = 15V, I_O = 0.5A, C_I = 0.33μF, C_O = 0.1μF, T_J = -40 to 125°C, unless otherwise specified)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Output Voltage	V _O	T _J = 25°C, I _O = 5mA ~ 1A	8.64	9.0	9.36	V
		V _I = 11.5V ~ 24V, I _O = 5mA ~ 1A	8.55	9.0	9.45	V
Line Regulation ⑧	ΔV _O	T _J = 25°C	V _I = 11.5V ~ 25V		180	mV
			V _I = 12V ~ 17V		90	
Load Regulation ⑧	ΔV _O	T _J = 25°C,	I _O = 5mA ~ 1A		180	mV
			I _O = 0.25A ~ 0.75A		90	
Quiescent Current	I _Q	T _J = 25°C			8.0	mA
Quiescent Current Change	ΔI _Q	I _O = 5mA ~ 1A			0.5	mA
		V _I = 11.5V ~ 26V			1.3	
Output Voltage Drift ⑨	ΔV / ΔT	I _O = 5mA		-1.0		mV/°C
Output Noise Voltage	V _N	10Hz ≤ f ≤ 100KHz		52		μV/V _O
Ripple Rejection ⑨	RR	f = 120Hz, V _I = 13V ~ 23V	56	71		dB
Short Circuit Current	I _{SC}	T _J = 25°C, V _I = 30V		230		mA
Output Resistance ⑨	R _O	f = 1kHz		17		mΩ
Peak Out Current ⑨	I _{PK}	T _J = 25°C		1.8		A
Dropout Voltage	V _d	T _J = 25°C, I _O = 1A		2.0		V

Note 8: Load and line regulation are specified at constant junction temperature. Changes in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Note 9: These parameters, although guaranteed, are not 100% tested in production.

Electrical Characteristics (7810AD/AT)

(V_I = 16V, I_O = 0.5A, C_I = 0.33μF, C_O = 0.1μF, T_J = -40 to 125°C, unless otherwise specified)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Output Voltage	V _O	T _J = 25°C, I _O = 5mA ~ 1A	9.60	10.0	10.40	V
		V _I = 12.5V ~ 25V, I _O = 5mA ~ 1A	9.50	10.0	10.50	V
Line Regulation ⑩	ΔV _O	T _J = 25°C	V _I = 12.5V ~ 25V		200	mV
			V _I = 13V ~ 25V		100	
Load Regulation ⑩	ΔV _O	T _J = 25°C,	I _O = 5mA ~ 1A		200	mV
			I _O = 0.25A ~ 0.75A		100	
Quiescent Current	I _Q	T _J = 25°C			8.0	mA
Quiescent Current Change	ΔI _Q	I _O = 5mA ~ 1A			0.5	mA
		V _I = 12.5V ~ 29V			1.0	
Output Voltage Drift ⑪	ΔV / ΔT	I _O = 5mA		-1.0		mV/°C
Output Noise Voltage	V _N	10Hz ≤ f ≤ 100KHz		58		μV/V _O
Ripple Rejection ⑫	RR	f = 120Hz, V _I = 13V ~ 23V	56	71		dB
Short Circuit Current	I _{SC}	T _J = 25°C, V _I = 30V		230		mA
Output Resistance ⑬	R _O	f = 1kHz		17		mΩ
Peak Out Current ⑭	I _{PK}	T _J = 25°C		1.8		A
Dropout Voltage	V _d	T _J = 25°C, I _O = 1A		2.0		V

Note 10: Load and line regulation are specified at constant junction temperature. Changes in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Note 11: These parameters, although guaranteed, are not 100% tested in production.

Electrical Characteristics (7812AD/AT)

($V_I = 19V$, $I_o = 0.5A$, $C_I = 0.33\mu F$, $C_O = 0.1\mu F$, $T_j = -40$ to $125^\circ C$, unless otherwise specified)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Output Voltage	V_o	$T_j = 25^\circ C$, $I_o = 5mA \sim 1A$	11.52	12.0	12.48	V
		$V_I = 14.5V \sim 27V$, $I_o = 5mA \sim 1A$	11.40	12.0	12.60	V
Line Regulation ⑫	ΔV_o	$T_j = 25^\circ C$ $I_o = 0.5A$	$V_I = 14.5V \sim 30V$		240	mV
			$V_I = 11.5V \sim 24V$		120	
Load Regulation ⑫	ΔV_o	$T_j = 25^\circ C$,	$I_o = 5mA \sim 1A$		240	mV
			$I_o = 0.25A \sim 0.75A$		120	
Quiescent Current	I_q	$T_j = 25^\circ C$			8.0	mA
Quiescent Current Change	ΔI_q	$I_o = 5mA \sim 1A$			0.5	mA
		$V_I = 14.5V \sim 30V$			1.0	
Output Voltage Drift ⑬	$\Delta V / \Delta T$	$I_o = 5mA$		-1.0		mV/ $^\circ C$
Output Noise Voltage	V_N	$10Hz \leq f \leq 100KHz$		76		$\mu V/V_o$
Ripple Rejection ⑬	RR	$f = 120Hz$, $V_I = 15V \sim 25V$	55	71		dB
Output Resistance ⑬	R_o	$f = 1kHz$		18		m Ω
Short Circuit Current	I_{SC}	$T_j = 25^\circ C$, $V_I = 30V$		230		mA
Peak Out Current ⑬	I_{PK}	$T_j = 25^\circ C$		1.8		A
Dropout Voltage	V_d	$T_j = 25^\circ C$, $I_o = 1A$		2.0		V

Note 12: Load and line regulation are specified at constant junction temperature. Changes in V_o due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Note 13: These parameters, although guaranteed, are not 100% tested in production.

Electrical Characteristics (7815AD/AT)

(V_I = 23V, I_O = 0.5A, C_I = 0.33μF, C_O = 0.1μF, T_J = -40 to 125°C, unless otherwise specified)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Output Voltage	V _O	T _J = 25°C, I _O = 5mA ~ 1A	14.40	15.0	15.60	V
		V _I = 17.5V ~ 30V, I _O = 5mA ~ 1A	14.25	15.0	15.75	V
Line Regulation ⑭	ΔV _O	T _J = 25°C I _O = 0.5A	V _I = 17.5V ~ 30V		300	mV
			V _I = 20V ~ 26V		150	
Load Regulation ⑭	ΔV _O	T _J = 25°C,	I _O = 5mA ~ 1A		300	mV
			I _O = 0.25A ~ 0.75A		150	
Quiescent Current	I _Q	T _J = 25°C			8.0	mA
Quiescent Current Change	ΔI _Q	I _O = 5mA ~ 1A			0.5	mA
		V _I = 17.5V ~ 30V			1.0	
Output Voltage Drift ⑮	ΔV / ΔT	I _O = 5mA		-1.0		mV/°C
Output Noise Voltage	V _N	10Hz ≤ f ≤ 100KHz		90		μV/V _O
Ripple Rejection ⑮	RR	f = 120Hz, V _I = 18.5V ~ 28.5V	54	70		dB
Output Resistance ⑮	R _O	f = 1kHz		19		mΩ
Short Circuit Current	I _{SC}	T _J = 25°C, V _I = 30V		230		mA
Peak Out Current ⑮	I _{PK}	T _J = 25°C		1.8		A
Dropout Voltage	V _d	T _J = 25°C, I _O = 1A		2.0		V

Note 14: Load and line regulation are specified at constant junction temperature. Changes in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Note 15: These parameters, although guaranteed, are not 100% tested in production.

Typical Characteristics




Figure 1. Peak Output Current




Figure 2. Dropout Voltage vs. Junction Temperature




Figure 3. Ripple Rejection Ratio vs. Output Voltage




Figure 4. Quiescent Current vs. Junction Temperature




Figure 8. Output Voltage vs. Input Voltage





Figure 9. Output Impedance (mΩ) vs. Output Voltage


Application circuit



Note 1: To specify an output voltage, substitute voltage value for "MXX".

Note 2: Bypass capacitors are recommended for optimum stability and transient response and should be located as close as possible to the regulators.

Marking Diagram



Ordering information


Model name	Package	Unit Weight	Base Quantity	Packing Quantity
78XXAD	TO-252	0.011oz(0.32g)	2500pcs/reel	5000pcs/box 25000pcs/Carton

Package Dimensions

TO-252

Dim	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	2.20	2.50	0.087	0.098
A1	0.00	0.12	0.000	0.005
A2	2.20	2.40	0.087	0.094
B	1.20	1.60	0.047	0.063
b	0.50	0.70	0.020	0.028
b1	0.70	0.90	0.028	0.035
c	0.40	0.60	0.016	0.024
c1	0.40	0.60	0.016	0.024
D	6.35	6.65	0.250	0.262
D1	5.20	5.40	0.205	0.213
E	5.40	5.70	0.213	0.224
e	2.20	2.40	0.087	0.094
e1	4.40	4.80	0.173	0.189
L	10.00	11.00	0.393	0.433
L1	2.70	3.10	0.106	0.122
L2	1.40	1.80	0.055	0.071
L3	0.90	1.50	0.035	0.059

Marking Diagram



Ordering information

Model name	Package	Unit Weight	Base Quantity	Packing Quantity
78XXAT	TO-220AB	0.07oz(1.96g)	50pcs/tube	1000PCS/Box 5000PCS/Carton

Package Dimensions

TO-220AB

Symbol	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	4.30	4.70	0.169	0.185
A1	2.52	2.82	0.099	0.111
b	0.71	0.91	0.028	0.036
b1	1.17	1.37	0.046	0.054
c	0.30	0.50	0.012	0.020
c1	1.17	1.37	0.046	0.054
D	9.90	10.20	0.390	0.402
E	8.50	8.90	0.335	0.350
E1	12.00	12.50	0.472	0.492
e	2.44	2.64	0.096	0.104
e1	4.88	5.28	0.192	0.208
F	2.60	2.80	0.102	0.110
L	13.20	13.80	0.520	0.543
L1	3.80	4.20	0.150	0.165
Φ	3.60	3.96	0.142	0.156