



Notes:

1. Pitch:11.5mm ,Poles:2-12P
2. Rated voltage/current:UL 300V/50A  
VDE 750V/57A
3. Operation temperatures:-40°C~+105°C
4. Withstanding Voltage:AC3000V/1Min
5. Insulation Resistance:5000MΩ/DC1000V
6. Wire Range:14~8AWG, 1.5~10mm<sup>2</sup>
7. Max. Torque Value:M3. 5, 8. 16kgf. cm
8. Undimensioned Tolerances:

Pitch range in mm			Nominal dimension range in mm							
	over 6	over 10		over 30	over 60	over 100	over 150		∩	
to 6	to 10	to 24	to 30	to 60	to 100	to 150			∇	
±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10		

3	GT12HS-Current carrier		XX	Zinc alloy	Cr <sup>3+</sup> Zn
2	GT12HS"-Screw		XX*2	Steel	Cr <sup>3+</sup> Zn
1	GT12HS-1.2- Housing		1	PA66	UL94V-2
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
	DF TO	DATE 14/11/12"	<b>Golten</b> 宁波冠泰电子有限公司 NINGBO GOLTEN ELECTRONICS CO.,LTD.		
	CHKD	DATE			
	MFD	DATE			
	APPVL	DATE			
TOLERANCES EXCEPT AS NOTED		MATERIAL :		NAME	
MM	±			GT12HS-1.2-XXP-1Y- 00A(H)	
.0 ±	±			DRAWING NO. GT12HS-E06	
.00 ±	±			/PART NO.	
.000 ±	±			SIZE A4	
ANGLES ± 1°		G.E :		REV	
THIRD ANGLE PROJECTION		FINISH:		SCALE : 1:1	
DO NOT SCALE DRAWING			SHEET 1		OF 1

8

7

6

5

4

3

2

1