

10W, wide input isolated & regulated dual/single output, DIP packaging, DC-DC converter



UL[®] CB CE Patent Protection RoHS



FEATURES

- Wide range of input voltage (4:1)
- Efficiency up to 88%
- No-load power consumption as low as 0.12W
- Isolation voltage : 1.5K VDC
- Operating temperature range: -40°C to +85°C
- Input under-voltage protection, output over-voltage protection, short circuit protection, output over-current protection
- Meet CISPR22/EN55022 CLASS A
- International standard pin-out
- A2S (wiring mounting) and A4S (TS35 rail mounting) products featuring anti-reverse connection for input
- Meet UL60950, EN60950 and IEC60950

URA_YMD-10WR3 & URB_YMD-10WR3 series products are of 10W output power, extremely wide range of voltage input of 9-36VDC, 18-75VDC, isolation voltage of 1500VDC, Input under-voltage protection, output over-voltage protection, output short circuit protection and output over-current protection with the bare component in compliance with CISPR22/EN55022 CLASS A; these products are widely used in fields such as industrial control, electric power, instruments and communication.

Selection Guide

Certification	Part No. ①	Input Voltage (VDC)		Output		Efficiency ③ (%) ,Min./Typ.) @ Full Load	Max. Capacitive Load ④ (μF)
		Nominal (Range)	Max. ②	Output Voltage (VDC)	Output Current (mA) (Max./Min.)		
UL/CE/CB	URA2405YMD-10WR3	24 (9-36)	40	±5	±1000/±50	81/83	1000
	URA2409YMD-10WR3			±9	±555/±28	84/86	680
	URA2412YMD-10WR3			±12	±416/±21	85/87	470
	URA2415YMD-10WR3			±15	±333/±16	85/87	330
	URA2424YMD-10WR3			±24	±208/±10	85/87	100
	URB2403YMD-10WR3			3.3	2400/120	77/79	2200
	URB2405YMD-10WR3			5	2000/100	81/83	2200
	URB2409YMD-10WR3			9	1111/56	84/86	680
	URB2412YMD-10WR3			12	833/42	85/87	470
	URB2415YMD-10WR3			15	667/33	85/87	330
	URB2424YMD-10WR3			24	416/21	86/88	100
	URA4805YMD-10WR3			48 (18-75)	80	±5	±1000/±50
	URA4812YMD-10WR3	±12	±416/±21			85/87	470
	URA4815YMD-10WR3	±15	±333/±16			85/87	330
	URA4824YMD-10WR3	±24	±208/±10			85/87	100
	URB4803YMD-10WR3	3.3	2400/120			77/79	2200
	URB4805YMD-10WR3	5	2000/100			81/83	2200
	URB4812YMD-10WR3	12	833/42			85/87	470
	URB4815YMD-10WR3	15	667/33			85/87	330
	URB4824YMD-10WR3	24	416/21			86/88	100

Notes:
 ① Part No. with suffix of "A2S" means chassis mounting and suffix of "A4S" means DIN-Rail mounting (e.g. URB2405YMD-10WR3A2S means chassis mounting; URB2405YMD-10WR3A4S means DIN-Rail mounting);
 ② Absolute maximum rating without damage on the converter, but it isn't recommended;
 ③ Efficiency is measured in nominal input voltage and rated output load; A2S (wiring) and A4S (rail) Model due to input reverse polarity protection, minimum efficiency greater than Min.-2 is qualified.
 ④ The capacitive loads of positive and negative outputs are identical.

Input Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Input Current (full load / no-load)	24VDC input	--	502/5	514/12	mA
	48VDC input	--	251/4	257/8	
Reflected Ripple Current	24VDC input	--	40	--	mA
	48VDC input	--	30	--	
Input Impulse Voltage (1sec. max.)	24VDC input	-0.7	--	50	VDC
	48VDC input	-0.7	--	100	
Starting Voltage	24VDC input	--	--	9	VDC
	48VDC input	--	--	18	
Input under-voltage Protection	24VDC input	5.5	6.5	--	VDC
	48VDC input ^①	14	15.5	--	
Starting Time	Nominal input& constant resistance load	--	10	--	ms
Input Filter		Pi filter			
Hot Plug		Unavailable			
Ctrl*	Module switch on	Ctrl suspended or connected to TTL high level (3.5-12VDC)			
	Module switch off	Ctrl pin connected to GND or low level (0-1.2VDC)			
	Input current when switched off	--	6	10	mA

Note: *The voltage of Ctrl pin is relative to input pin GND.

Output Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Output Voltage Accuracy	Positive output	--	±1	±3	%
	Negative output				
Balance of Output Voltage	Dual output, balanced load	--	±0.5	±1.5	%
Line Regulation	Full load, the input voltage is from low voltage to high voltage	Positive output	±0.2	±0.5	
		Negative output	±0.5	±1	
Load Regulation	5%-100% load	Positive output	±0.5	±1	
		Negative output	--	±0.5	
Cross Regulation	Dual output, main circuit with 50% load, auxiliary circuit with 10%-100% load	--	--	±5	
Transient Recovery Time	25% load step change	--	300	500	μs
Transient Response Deviation		--	±3	±5	%
Temperature Drift Coefficient	Full load	--	--	±0.03	%/°C
Ripple & Noise*	20MHz bandwidth	--	40	80	mV p-p
Over-voltage Protection	Input voltage range	110	--	160	%Vo
Over-current Protection		110	140	190	%Io
Short circuit Protection		Continuous, self-recovery			

Note: * Ripple and noise tested with "parallel cable" method, please see *DC-DC Converter Application Notes* for specific operation methods.

General Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Insulation Voltage	Input-output, with the test time of 1 minute and the leak current lower than 1mA	1500	--	--	VDC
Insulation Resistance	Input-output, insulation voltage 500VDC	1000	--	--	MΩ
Isolation Capacitance	Input-output, 100KHz/0.1V	--	1000	--	pF
Operating Temperature	see Fig. 1	-40	--	85	°C
Storage Temperature		-55	--	125	
Storage Humidity	Non-condensing	5	--	95	%RH
Lead Temperature	Welding spot is 1.5mm away from the casing, 10 seconds	--	--	300	
Vibration		10-55Hz, 10G, 30 Min. along X, Y and Z			

Switching Frequency	PWM mode	--	350	--	KHz
MTBF	MIL-HDBK-217F@25°C	1000	--	--	K hours

Note:*This series of products with reduced frequency technology,The switching frequency of the full test, when the load is light, the switching frequency decline.

Physical Specifications

Casing Material	Aluminum alloy				
Package Dimensions	Horizontal package	25.40*25.40*11.70 mm			
	A2S chassis mounting	76.00*31.50*21.20 mm			
	A4S DIN-rail mounting	76.00*31.50*25.80 mm			
Weight	Horizontal package/A2S wiring package/A4S rail package	15.00g/35.00g/55.00g (Typ.)			
Cooling method	Free air convection				

EMC Specifications

EMI	Conducted disturbance	CISPR22/EN55022 CLASS A (Bare component)/ CLASS B (see Fig.3-② for recommended circuit)			
	Radiated emission	CISPR22/EN55022 CLASS A (Bare component)/ CLASS B (see Fig.3-② for recommended circuit)			
EMS	Electrostatic discharge	IEC/EN61000-4-2	Contact ±4KV	perf. Criteria B	
	Radiation immunity	IEC/EN61000-4-3	10V/m	perf. Criteria A	
	EFT	IEC/EN61000-4-4	±2KV (see Fig.3-① for recommended circuit)	perf. Criteria B	
	Surge Immunity	IEC/EN61000-4-5	±2KV (see Fig.3-① for recommended circuit)	perf. Criteria B	
	Conducted disturbance immunity	IEC/EN61000-4-6	3 Vr.m.s	perf. Criteria A	
	Immunities of voltage dip, drop and short interruption	IEC/EN61000-4-29	0-70%	perf. Criteria B	

Product Characteristic Curve








Fig. 1





Design Reference

1. Typical application

All the DC/DC converters of this series are tested according to the recommended circuit (see Fig. 2) before delivery. If it is required to further reduce input and output ripple, properly increase the input & output of additional capacitors Cin and Cout or select capacitors of low equivalent impedance provided that the capacitance is no larger than the max. capacitive load of the product.




Fig. 2

Vin	24V	48V
Cin1	100µF	10µF ~47µF
Cout	10µF	

2. EMC solution-recommended circuit




Fig. 3

Notes: Part ① in the Fig. 3 is used for EMS test and part ② for EMI filtering; selected based on needs.

Parameter description:

Model	Vin:24V	Vin:48V
FUSE	Choose according to actual input current	
MOV	S14K35	S14K60
C0	330µF/50V	330µF/100V
C1	1µF/50V	1µF/100V
C2	Refer to the Cout in Fig.2	
LDM1	4.7µH	
CY1/CY2	1nF/2KV	

EMC solution-recommended circuit PCB layout





Fig. 4

Note: the min. distance of the bonding pads between input & output isolation capacitors (CY1/CY2) shall be ≥ 2mm.

3. The product does not support output in parallel with power per liter


4. For more information please find the application notes on www.mornsun-power.com

Dimensions and Recommended Layout




Note:
Unit :mm[inch]
Pin diameter tolerances :±0.10[±0.004]
General tolerances:±0.50[±0.020]

URA_YMD-10WR3A2S & URB_YMD-10WR3A2S Dimensions



URA_YMD-10WR3A4S & URB_YMD-10WR3A4S Dimensions

THIRD ANGLE PROJECTION 



Pin-Out						
Pin	1	2	3	4	5	6
Single	Ctrl	GND	Vin	0V	NC	+Vo
Dual	Ctrl	GND	Vin	-Vo	0V	+Vo

Note:
 Unit:mm[inch]
 Wire range:24~12 AWG
 General tolerances:±0.50[±0.020]

- Note:
1. Packing Information please refer to 'Product Packing Information'. Packing bag number : 58210003(DIP),58220022(A2S/A4S package);
 2. Recommend to use module with more than 5% load, if not, the ripple of the product may exceeds the specification, but does not affect the reliability of the product;
 3. The unbalance degree of the recommended dual output module load: $\leq 5\%$; if the degree exceeds $\pm 5\%$, then the product performances cannot be guaranteed to comply with all the performance indicators in the manual, and please directly contact our technicians for specific information;
 4. The max. capacitive load should be tested within the input voltage range and under full load conditions;
 5. Unless otherwise specified, data in this datasheet should be tested under the conditions of $T_a=25^\circ\text{C}$, humidity<75% when inputting nominal voltage and outputting rated load;
 6. All index testing methods in this datasheet are based on our Company's corporate standards;
 7. The performance indexes of the product models listed in this datasheet are as above, but some indexes of non-standard model products will exceed the above-mentioned requirements, and please directly contact our technicians for specific information;
 8. We can provide product customization service;
 9. Specifications of this product are subject to changes without prior notice.

Mornsun Guangzhou Science & Technology Co., Ltd.

Address: No. 5, Kehui St. 1, Kehui Development Center, Science Ave., Guangzhou Science City, Luogang District, Guangzhou, P. R. China
 Tel: 86-20-38601850-8801 Fax: 86-20-38601272 E-mail: info@mornsun.cn