

Revised Record




1.0

New issue

2012-06-21

INTERFACE:

1	VSS
2	VCC(5.0V)
3	V0
4	RS
5	RW
6	E
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	A
16	K



NOTES:

- | | |
|----------------------------|----------------------------------|
| 01. DISPLAY TYPE: | FSTN/POSITIVE/TRANSFLECTIVE RoHS |
| 02. OPERATING VOLTAGE: | VOP=4.7V,VDD=5.0V |
| 03. OPERATING TEMPERATURE: | 0°C~+50°C |
| 04. STORAGE TEMPERATURE: | -10°C~+60°C |
| 05. DRIVE MODE: | 1/16DUTY,1/5BIAS |
| 06. VIEWING DIRECTION: | 6:00 |
| 07. DRIVE IC: | AIP31066 |
| 08. CONNECTOR: | ZEBER |
| 09. BACKLIGHT: | --- |
| 10. CUSTOMER'S PART ID: | BLAZE_STANDARD_PRODUCT |


BLAZE Blaze Display Technology Co.,Ltd.

DESIGNED BY: BDT-26

BCB1602-03B-SERIES

VERSION: 1.0

CHECKED BY: BDT-04



PAGE 1 OF 1

APPROVED BY: BDT-01

UNIT: mm

Website: <http://www.blazedisplay.com>

DATE: 2012-06-21