



YETDA INDUSTRY LTD.

Technical Data Sheet

MODEL NO : S776YNW4-P

3528 Package 2.8*3.2mm Chip LEDs

Features :

- Compatible with automatic placement equipment
- Compatible with reflow solder process

Applications :

- Indicators
- Automotive : backlighting in dashboard and switch
- Backlight for LCD

Dice material	Emitted color	Lens Color
InGaN	White	Water Clear

Electrical/Optical Characteristics(Ta=25°C)

Parameter	Test Condition	Symbol	Value			Unit
			Min	Typ	Max	
Color Coordinates	If=150mA	x		0.31		
		y		0.32		
Forward voltage	If=150mA	Vf	3.0		3.8	V
Cool Temperature	If=150mA	TC		6500		K
Luminous flux (lm)	If=150mA	lm	40	45		
Luminous Intensity	If=150mA	Iv		13000		mcd
Viewing angle at 50% Iv	If=150mA	2θ 1/2		120		Deg
Reverse current	Vr=5V	Ir			10	μA

Absolute Maximum Ratings(Ta=25°C)

Parameter	Symbol	Value	Unit
Power dissipation	Pd	500	mW
Forward current	If	150	mA
Reverse voltage	Vr	5	V
Operating temperature range	Top	-40 ~+80	°C
Storage temperature range	Tstg	-40 ~+100	°C
Peak pulsing current (1/8 duty f=1kHz)	I _{fp}	200	mA



YETDA INDUSTRY LTD.

PACKAGING DIMENSIONS

