


**■Features**


- High Luminous Super Flux Output
- 5  $\phi$  Standard Directivity
- Long Lifetime Operation
- Superior Weather-resistance
- UV Resistant Epoxy
- Water Clear Type

**■Applications**

- Automotive Dashboard Lighting
- Small Area Illuminations
- Back Lighting
- Other Lighting

**■Outline Dimension**

**■Absolute Maximum Rating**
**(Ta=25°C)**

Item	Symbol	Value	Unit
DC Forward Current	$I_F$	100	mA
Pulse Forward Current*	$I_{FP}$	120	mA
Reverse Voltage	$V_R$	5	V
Power Dissipation	$P_D$	380	mW
Operating Temperature	$T_{opr}$	-30 ~ +85	°C
Storage Temperature	$T_{stg}$	-40 ~ +100	°C
Lead Soldering Temperature	$T_{sol}$	260°C/5sec	-

**■Directivity**


\*Pulse width Max.10ms Duty ratio max 1/10

**■Electrical -Optical Characteristics**
**(Ta=25°C)**

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
DC Forward Voltage	$V_F$	$I_F=80mA$	2.9	3.2	3.8	V
DC Reverse Current	$I_R$	$V_R=5V$	-	-	40	$\mu A$
Domi. Wavelength*	$\lambda_D$	$I_F=80mA$	520	525	530	nm
Luminous Intensity*	$I_v$	$I_F=80mA$	8000	10000	-	mcd
50% Power Angle	$2\theta_{1/2}$	$I_F=80mA$	-	120	-	deg

\*1 Tolerance of dominant wavelength  $\pm 1nm$

\*2 Tolerance of luminous intensity is  $\pm 15\%$