



SPECIFICATIONS

Current Rating:3Amps
 Insulation Resistance:1000M Ω min
 Withstanding Voltage: 1000VAC
 Contact Resistance:20m Ω max
 Operating Temperature:-40° C to+105° C
 Standard:PBT
 Contact Material:Brass
 Contact Plating:Au or Sn Over Ni
 Max.Processing Temp:200 °Cfor30-60second
 (220 °Cfor10second)

Code Description

CH-254-IC-XX-R-A-W-I

(1) (2) (3) (4) (5) (6) (7)

- (1) Pin Spacing: 254=2.54mm
- (2) Product Name: IC=Round Hole
- (3) No. of Pins Per Row:6-64
- (4) ContactType:S=Straight;R=Right/Angle;N=SMT
- (5) Insulator Material Option:
 A=BK-PBT;B=BK-PA6T;C=BK-PA46;D=BK-LCP;S=Special
- (6) W=Wite N=Narrow
- (7) I=Import class;D=Domestic class



Position	Dimension			
	A	B	C	D
24	30.48	27.94	17.78	15.24
28	35.56	33.02	17.78	15.24
32	40.64	38.10	17.78	15.24
40	50.80	48.26	17.78	15.24
42	53.34	51.00	17.78	15.24
48	40.96	58.42	17.78	15.24
64	81.28	78.74	17.78	15.24

UNLESS OTHERWISE SPECIFIED TOLERANCE		DRAWN NAME: CH-254-IC-XX-R-A-W-D			
X	:±0.3	X°	:±5°		
X.X	:±0.2	X.X°	:±1°		
X.XX	:±0.2	X.XX°	:±0.5°		
SIZE	A4	SCALE	N:1	PROJECT	
REV	A	UNIT	mm	PROJECT	⊕ PAGE 1/1
CHECKED	LIU SHENG HUI	DATE	05/28	CHECKED	DATE /