



ITEM	Part Name	Material
①	Static plate	Copper alloy
②	Movable	Copper alloy
③	Key	POM
④	Cover	PA66
⑤	Case	PA66
⑥	Spring	Stainless steel
⑦	Contact	Au Alloy

Specification :

1. Rating: 12VAC/DC Max, 2V DC Min; 10mA AC/DC Max, 10  $\mu$ A DC Min.
2. Contact resistance: 200m $\Omega$  Max.
3. Insulation resistance: 100M $\Omega$  Min (DC 100V).
4. Withstand voltage: AC 100V(50° 60Hz) for 1 minute.
5. Bounce time: 5ms Max. (at 16 in./sec. actuation speed).
6. Operation force: 60  $\pm$  15gf.
7. Pretravel: 2.0  $\pm$  0.6mm.
8. Total travel: 4.0mm Max.
9. Operation life: 50,000,000 cycles min.

LTR	DESCRIPTION	DATE	CHANGE	APPL'
$\Delta$				
$\Delta$				
$\Delta$				

符合ROHS标准

**XKB INDUSTRIAL PRECISION CO., LIMITED**

For and on behalf of SINGAPORES  
**XKB INDUSTRIAL PRECISION CO., LIMITED**  
 香港星坤工业有限公司

PRODUCT: 键盘开关  
 DWG NO: XKB4S-X-RD-X-5-0-0  
 SCALE: REV:

CHK	DATE	ALL DIMENSIONS ARE IN MILLIMETER
APL		TOLERANCES CLASS: SHEET: 01