



## Thyristor Surface Mount, Phase Control SCR, 8 A


**D<sup>2</sup>PAK (TO-263AB)**


### FEATURES

- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C
- AEC-Q101 qualified
- Meets JESD 201 class 1A whisker test
- Flexible solution for reliable AC power rectification
- Easy control peak current at charger power up to reduce passive / electromechanical components
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
 COMPLIANT  
 HALOGEN  
**FREE**

### APPLICATIONS

- On-board and off-board EV / HEV battery chargers
- Renewable energy inverters

### DESCRIPTION

The VS-12TTS08SLHM3 high voltage series of silicon controlled rectifiers are specifically designed for medium power switching and phase control applications.

### PRIMARY CHARACTERISTICS

|                       |                               |
|-----------------------|-------------------------------|
| $I_{T(AV)}$           | 8 A                           |
| $V_{DRM}/V_{RRM}$     | 800 V                         |
| $V_{TM}$              | 1.2 V                         |
| $I_{GT}$              | 15 mA                         |
| $T_J$                 | -40 to +125 °C                |
| Package               | D <sup>2</sup> PAK (TO-263AB) |
| Circuit configuration | Single SCR                    |

### OUTPUT CURRENT IN TYPICAL APPLICATIONS

| APPLICATIONS   | SINGLE-PHASE BRIDGE | THREE-PHASE BRIDGE | UNITS |
|--|---------------------|--------------------|-------|
| Capacitive input filter $T_A = 55$ °C, $T_J = 125$ °C, common heatsink of 1 °C/W | 13.5                | 17                 | A     |

### MAJOR RATINGS AND CHARACTERISTICS

| PARAMETER         | TEST CONDITIONS     | VALUES      | UNITS |
|-------------------|---------------------|-------------|-------|
| $I_{T(AV)}$       | Sinusoidal waveform | 8           | A     |
| $I_{T(RMS)}$      |                     | 12.5        |       |
| $V_{RRM}/V_{DRM}$ |                     | 800         | V     |
| $I_{TSM}$         |                     | 110         | A     |
| $V_T$             | 8 A, $T_J = 25$ °C  | 1.2         | V     |
| dV/dt             |                     | 150         | V/μs  |
| dI/dt             |                     | 100         | A/μs  |
| $T_J$             | Range               | -40 to +125 | °C    |

### VOLTAGE RATINGS

| PART NUMBER     | $V_{RRM}$ , MAXIMUM PEAK REVERSE VOLTAGE<br>V | $V_{DRM}$ , MAXIMUM PEAK DIRECT VOLTAGE<br>V | $I_{RRM} / I_{DRM}$<br>AT 125 °C<br>mA |
|-----------------|---|--|--|
| VS-12TTS08SLHM3 | 800   | 800  | 5.0                                    |



| ABSOLUTE MAXIMUM RATINGS                            |                 |   |                                   |               |    |
|---|-----------------|---|-----------------------------------|---------------|----|
| PARAMETER   | SYMBOL          | TEST CONDITIONS   | VALUES                            | UNITS         |    |
| Maximum average on-state current                    | $I_{T(AV)}$     | $T_C = 108\text{ }^\circ\text{C}$ , 180° conduction, half sine wave                               | 8                                 | A             |    |
| Maximum RMS on-state current                        | $I_{T(RMS)}$    |   | 12.5                              |               |    |
| Maximum peak one-cycle non-repetitive surge current | $I_{TSM}$       | 10 ms sine pulse, rated $V_{RRM}$ applied, $T_J = 125\text{ }^\circ\text{C}$                      | 95                                |               |    |
|   |                 | 10 ms sine pulse, no voltage reapplied, $T_J = 125\text{ }^\circ\text{C}$                         | 110                               |               |    |
| Maximum $I^2t$ for fusing                           | $I^2t$          | 10 ms sine pulse, rated $V_{RRM}$ applied, $T_J = 125\text{ }^\circ\text{C}$                      | 45                                | $A^2s$        |    |
|   |                 | 10 ms sine pulse, no voltage reapplied, $T_J = 125\text{ }^\circ\text{C}$                         | 64                                |               |    |
| Maximum $I^2\sqrt{t}$ for fusing                    | $I^2\sqrt{t}$   | $t = 0.1\text{ ms to } 10\text{ ms}$ , no voltage reapplied, $T_J = 125\text{ }^\circ\text{C}$    | 640                               | $A^2\sqrt{s}$ |    |
| Maximum on-state voltage drop                       | $V_{TM}$        | 8 A, $T_J = 25\text{ }^\circ\text{C}$   | 1.2                               | V             |    |
| On-state slope resistance                           | $r_t$           | $T_J = 125\text{ }^\circ\text{C}$   | 16.2                              | $m\Omega$     |    |
| Threshold voltage                                   | $V_{T(TO)}$     |   | 0.87                              | V             |    |
| Maximum reverse and direct leakage current          | $I_{RM}/I_{DM}$ | $V_R = \text{rated } V_{RRM} / V_{DRM}$   | $T_J = 25\text{ }^\circ\text{C}$  | 0.05          | mA |
|   |                 |   | $T_J = 125\text{ }^\circ\text{C}$ | 5.0           |    |
| Typical holding current                             | $I_H$           | Anode supply = 6 V, resistive load, initial $I_T = 1\text{ A}$ , $T_J = 25\text{ }^\circ\text{C}$ | 30                                |               |    |
| Typical latching current                            | $I_L$           | Anode supply = 6 V, resistive load, $T_J = 25\text{ }^\circ\text{C}$                              | 50                                |               |    |
| Maximum rate of rise of off-state voltage           | $dV/dt$         | $T_J = T_J \text{ max.}$ , linear to 80 %, $V_{DRM} = R_g - k = \text{open}$                      | 150                               | $V/\mu s$     |    |
| Maximum rate of rise of turned-on current           | $dI/dt$         |   | 100                               | $A/\mu s$     |    |

| TRIGGERING                                  |             |   |        |       |
|---|-------------|---|--------|-------|
| PARAMETER                                   | SYMBOL      | TEST CONDITIONS   | VALUES | UNITS |
| Maximum peak gate power                     | $P_{GM}$    |   | 8.0    | W     |
| Maximum average gate power                  | $P_{G(AV)}$ |   | 2.0    |       |
| Maximum peak positive gate current          | $+I_{GM}$   |   | 1.5    | A     |
| Maximum peak negative gate voltage          | $-V_{GM}$   |   | 10     | V     |
| Maximum required DC gate current to trigger | $I_{GT}$    | Anode supply = 6 V, resistive load, $T_J = -65\text{ }^\circ\text{C}$ | 20     | mA    |
|   |             | Anode supply = 6 V, resistive load, $T_J = 25\text{ }^\circ\text{C}$  | 15     |       |
|   |             | Anode supply = 6 V, resistive load, $T_J = 125\text{ }^\circ\text{C}$ | 10     |       |
| Maximum required DC gate voltage to trigger | $V_{GT}$    | Anode supply = 6 V, resistive load, $T_J = -65\text{ }^\circ\text{C}$ | 1.2    | V     |
|   |             | Anode supply = 6 V, resistive load, $T_J = 25\text{ }^\circ\text{C}$  | 1      |       |
|   |             | Anode supply = 6 V, resistive load, $T_J = 125\text{ }^\circ\text{C}$ | 0.7    |       |
| Maximum DC gate voltage not to trigger      | $V_{GD}$    | $T_J = 125\text{ }^\circ\text{C}$ , $V_{DRM} = \text{rated value}$    | 0.2    |       |
| Maximum DC gate current not to trigger      | $I_{GD}$    |   | 0.1    | mA    |

| SWITCHING                     |          |                                   |        |         |
|-------------------------------|----------|-----------------------------------|--------|---------|
| PARAMETER                     | SYMBOL   | TEST CONDITIONS                   | VALUES | UNITS   |
| Typical turn-on time          | $t_{gt}$ | $T_J = 25\text{ }^\circ\text{C}$  | 0.8    | $\mu s$ |
| Typical reverse recovery time | $t_{rr}$ | $T_J = 125\text{ }^\circ\text{C}$ | 3      |         |
| Typical turn-off time         | $t_q$    |                                   | 100    |         |



| THERMAL AND MECHANICAL SPECIFICATIONS           |                |  |             |       |
|---|----------------|--|-------------|-------|
| PARAMETER                                       | SYMBOL         | TEST CONDITIONS                          | VALUES      | UNITS |
| Maximum junction and storage temperature range  | $T_J, T_{Stg}$ |  | -40 to +125 | °C    |
| Maximum thermal resistance, junction to case    | $R_{thJC}$     | DC operation                             | 1.5         | °C/W  |
| Maximum thermal resistance, junction to ambient | $R_{thJA}$     |  | 62          |       |
| Typical thermal resistance, case to heatsink    | $R_{thCS}$     | Mounting surface, smooth, and greased    | 0.5         |       |
| Approximate weight                              |                |  | 2           | g     |
|   |                |  | 0.07        | oz.   |
| Marking device                                  |                | Case style D <sup>2</sup> PAK (TO-263AB) | 12TTS08SH   |       |




Fig. 1 - Current Rating Characteristics




Fig. 3 - On-State Power Loss Characteristics




Fig. 2 - Current Rating Characteristics




Fig. 4 - On-State Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - On-State Voltage Drop Characteristics




Fig. 8 - Thermal Impedance  $Z_{thJC}$  Characteristics



ORDERING INFORMATION TABLE

|             |     |    |   |   |   |    |   |   |   |    |
|-------------|-----|----|---|---|---|----|---|---|---|----|
| Device code | VS- | 12 | T | T | S | 08 | S | L | H | M3 |
|             | 1   | 2  | 3 | 4 | 5 | 6  | 7 | 8 | 9 | 10 |

- 1** - Vishay Semiconductors product
- 2** - Current rating (12.5 A)
- 3** - Circuit configuration:  
T = single thyristor
- 4** - Package:  
T = D<sup>2</sup>PAK (TO-263AB)
- 5** - Type of silicon:  
S = standard recovery rectifier
- 6** - Voltage rating (08 = 800 V)
- 7** - S = surface mountable
- 8** - L = tape and reel (left oriented), for different orientation contact factory
- 9** - H = AEC-Q101 qualified
- 10** - Environmental digit:  
M3 = halogen-free, RoHS-compliant, and terminations lead (Pb)-free

| ORDERING INFORMATION (Example) |                  |                        |                       |
|--------------------------------|------------------|------------------------|-----------------------|
| PREFERRED P/N                  | QUANTITY PER T/R | MINIMUM ORDER QUANTITY | PACKAGING DESCRIPTION |
| VS-12TTS08SLHM3                | 800              | 800                    | 13" diameter reel     |

| LINKS TO RELATED DOCUMENTS |  |
|----------------------------|--|
| Dimensions                 | <a href="http://www.vishay.com/doc?95046">www.vishay.com/doc?95046</a> |
| Part marking information   | <a href="http://www.vishay.com/doc?95444">www.vishay.com/doc?95444</a> |
| Packaging information      | <a href="http://www.vishay.com/doc?96317">www.vishay.com/doc?96317</a> |

## D<sup>2</sup>PAK

### DIMENSIONS in millimeters and inches

Conforms to JEDEC® outline D<sup>2</sup>PAK (SMD-220)




| SYMBOL | MILLIMETERS |       | INCHES |       | NOTES | SYMBOL | MILLIMETERS |       | INCHES    |       | NOTES |
|--------|-------------|-------|--------|-------|-------|--------|-------------|-------|-----------|-------|-------|
|        | MIN.        | MAX.  | MIN.   | MAX.  |       |        | MIN.        | MAX.  | MIN.      | MAX.  |       |
| A      | 4.06        | 4.83  | 0.160  | 0.190 |       | D1     | 6.86        | 8.00  | 0.270     | 0.315 | 3     |
| A1     | 0.00        | 0.254 | 0.000  | 0.010 |       | E      | 9.65        | 10.67 | 0.380     | 0.420 | 2, 3  |
| b      | 0.51        | 0.99  | 0.020  | 0.039 |       | E1     | 7.90        | 8.80  | 0.311     | 0.346 | 3     |
| b1     | 0.51        | 0.89  | 0.020  | 0.035 | 4     | e      | 2.54 BSC    |       | 0.100 BSC |       |       |
| b2     | 1.14        | 1.78  | 0.045  | 0.070 |       | H      | 14.61       | 15.88 | 0.575     | 0.625 |       |
| b3     | 1.14        | 1.73  | 0.045  | 0.068 | 4     | L      | 1.78        | 2.79  | 0.070     | 0.110 |       |
| c      | 0.38        | 0.74  | 0.015  | 0.029 |       | L1     | -           | 1.65  | -         | 0.066 | 3     |
| c1     | 0.38        | 0.58  | 0.015  | 0.023 | 4     | L2     | 1.27        | 1.78  | 0.050     | 0.070 |       |
| c2     | 1.14        | 1.65  | 0.045  | 0.065 |       | L3     | 0.25 BSC    |       | 0.010 BSC |       |       |
| D      | 8.51        | 9.65  | 0.335  | 0.380 | 2     | L4     | 4.78        | 5.28  | 0.188     | 0.208 |       |

#### Notes

- Dimensioning and tolerancing per ASME Y14.5 M-1994
- Dimension D and E do not include mold flash. Mold flash shall not exceed 0.127 mm (0.005") per side. These dimensions are measured at the outmost extremes of the plastic body
- Thermal pad contour optional within dimension E, L1, D1 and E1
- Dimension b1 and c1 apply to base metal only
- Datum A and B to be determined at datum plane H
- Controlling dimension: inch
- Outline conforms to JEDEC® outline TO-263AB



## D<sup>2</sup>PAK



Example: This is a xxxxxx <sup>(1)</sup> with assembly lot code AC, assembled on WW 02, 2010

### Note

<sup>(1)</sup> If part number contain "H" as last digit, product is AEC-Q101 qualified

| ENVIRONMENTAL NAMING CODE (Z) | PRODUCT DEFINITION   |
|-------------------------------|--|
| A                             | Termination lead (Pb)-free                                   |
| B                             | Totally lead (Pb)-free                                       |
| E                             | RoHS-compliant and termination lead (Pb)-free                |
| F                             | RoHS-compliant and totally lead (Pb)-free                    |
| M                             | Halogen-free, RoHS-compliant, and termination lead (Pb)-free |
| N                             | Halogen-free, RoHS-compliant, and totally lead (Pb)-free     |
| G                             | Green  |



## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.