




**Material :**

- (a) Housing : PA66(UL94V-0)
- (b) Button : POM(UL94HB)
- (c) Spring : Stainless Steel
- (d) Clamp : Phosphor Bornze
- (e) Cover : PA66(UL94V-0)

**Electrical :**

- 1.Rated Voltage : 300V UL IEC
- 2.Rated Current : 10A 320V
- 3.Wire Range: 26-12AWG 20A
- 4.Stripping Length : 7-8mm 2.5mm<sup>2</sup>
- 5.Withstanding Voltage : AC1600V/1Min.
- 6.Operating Temperature : -40 °C~+105°C
- 7.RoHS Compliance
- 8.Safety Approval :
- 9.Undimensioned Tolerances:



Pitch Range In mm		Nominal Dimension Range In mm					Tolerances	
≤6	6 ~ 10	10 ~ 24	≤30	30 ~ 60	60 ~ 100	100 ~ 150	>150	0.05/10
±0.10	±0.15	±0.25	±0.20	±0.30	±0.50	±0.70	±1.00	±0.1°



2EGTKD - 5.08 -XXP - X X - XX AH

①                      ②                      ③                      ④                      ⑤                      ⑥                      ⑦

- ① Series NO.
- ② Pitch
- ③ Poles  
02 02Contacts  
03 03Contacts  
...  
24 24Contacts
- ④ 1 Single Pitch  
2 Double Pitch
- ⑤ Color: 1 Grey  
2 Blue  
3 Black  
4 Green(Standard For AH)  
5 Orange  
6 Red  
7 Transparent  
8 Yellow  
9 White
- ⑥ Customer Request: 00--Standard
- ⑦ AH--Standard(PA66)



DETACHED LISTS	<b>Grolten</b> 宁波冠泰电子有限公司 NINGBO GOLTEN ELECTRONICS CO., LTD.													
	APPD: MA_8/13/16'	PART NO. 2EGTKD-5.08-XXP-XX-00AH												
	CHKD: Yu_8/12/16'													
	DRFT: Chen_8/11/16'													
 THIRD ANGLE PROJECTION		<table border="1"> <tr> <td>DRAWING NO.</td> <td>REV</td> <td>1</td> </tr> <tr> <td></td> <td>SHEET</td> <td>1/1</td> </tr> <tr> <td>MM (INCH)</td> <td>DO NOT SCALE DRAWING</td> <td>SCALE</td> </tr> <tr> <td></td> <td></td> <td>1/1</td> </tr> </table>	DRAWING NO.	REV	1		SHEET	1/1	MM (INCH)	DO NOT SCALE DRAWING	SCALE			1/1
DRAWING NO.	REV	1												
	SHEET	1/1												
MM (INCH)	DO NOT SCALE DRAWING	SCALE												
		1/1												