

30W AC-DC Single Output Desktop Type EA1040 series



- ✓ CEC Efficiency Regulations Compliance
- ✓ RoHS Compliance
- ✓ IEC320 C8 (2PIN)
- ✓ Over Current Protective Installation
- ✓ Over Voltage Protective Installation
- ✓ Protection Type: Auto-recovery
- ✓ Application: POS,LCD, Printer,IT, Scanner,NB...

Specification

Parametr	Model	EA10402D
Output Voltage		12V
Output Rating (Max.)		30W
Output Current (Max.)		2,5A
Input Voltage (Limit)		AC 90-264V
Input Frequency		47~63Hz
Line Regulation		± 2% MAX
Load Regulation		± 5%
Ripple & Noise		2% Max.
Efficiency		81%
Active PFC		No
Over Voltage Protection		Yes
Over Current Protection		Yes
Operating Temperature		0~40°C
Storage Temperature		-20~85°C
Class I or Class II		Class II
Safety Standards		UL60950-1,EN60950-1,IEC60950-1
Safety/EMC		UL/CUL, FCC, CE, TUV, CB, PSE
MTBF		30 000 hours
LED Indication		No
Dimensions		(L. x W. x H.): 85.5 x 35.7 x 25.7 mm
Weight		160 g
Standard Plug		2.1 / 5.5 mm

30W AC-DC Single Output Desktop Type EA1040 series

